

Pointe®

It's very bright and super-fast with a sharp parallel beam that cuts through the air and across video with ease.

It can project a static or rotating glass gobo to produce precision in-air and surface images with an even focal plane. Tight or at full 20 degree zoom, the output is crystal clear and brilliant. Add in either rotating, 6 way linear or 8 way circular, prisms to create wide reaching effects across any set. Drop in the frost filter and use any of the 13 rich colours to create a smooth even wash. The Pointe has an output far greater in size, quality and power than seems possible from it's small, lightweight body - due to the efficient short arc 280 W discharge source and the Robe optical configuration. This new technology fixture even travels efficiently in a case of 4 and will cover all your needs - Beam, Spot, Wash, FX - there is no point in using any other fixture.



Light source

Osram Sirius HRI 280W RO

Light output

Beam mode: 9.870 lm, 82.400 lx @ 20 m

Spot mode: 5.150 lm, 90.000 lx @ 5 m

Zoom range

2, 5° - 10° Beam mode, 5° - 20° Spot mode

Effects

rotating and static gobo wheel, circular 8-facet and linear 6-facet prism

Technical Specification

SOURCE

- Lamp: Discharge short arc lamp with integrated reflector
- Approved model: Osram Sirius HRI 280 W RO
- Lamp Life Expectancy: Standard mode (280 W) - 2.000 hrs, Eco mode (230 W) - 3.000 hrs
- Control: Automatic and remote on/off
- Ballast: Electronic

OPTICAL SYSTEM

1. Light Output:

- Beam mode: 82,400 lx @ 20 m distance
- Spot mode: 90,000 lx @ 5 m distance
- Dichroic glass reflector integrated with the lamp for maximising the light efficiency
- Zoom range: 2.5°-10° beam application; 5° - 20° spot application

ELECTROMECHANICAL EFFECTS

- Colour wheel: 13 dichroic filters + white
- Rotating Gobo wheel: 9 rotating, indexable and replaceable "SLOT&LOCK" glass gobos + open
- Static Gobo wheel: 14 gobos + open
- Prism 1: 8-facet circular prism rotating in both directions at different speeds
- Prism 2: 6-facet linear prism rotating in both directions at different speeds
- Frost effect: Separate, variable
- Dimmer/Shutter: Full range dimming and variable strobe effect
- Motorized zoom and focus
- Pan: 540°
- Tilt: 270°

CONTROL AND PROGRAMMING

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2
- Optional wireless version available: CRMX™ technology from Lumen Radio
- Control channels: 24, 16, 30
- 3 DMX protocol modes
- 3-editable programs, each up to 100 steps
- Stand-alone operation
- QVGA Robe touch screen with battery backup gravitation sensor for auto screen positioning operation memory service log with RTC
- Pan/Tilt resolution: 8 or 16 bit
- Movement control: Tracking and vector
- Colour wheel positioning: 8 or 16bit
- Rotating gobo wheel positioning: 8 bit
- Gobo indexing & rotation: 8 or 16bit
- Static gobo wheel positioning: 8 bitt
- Prism indexing & rotation: 8 bit

- Frost: 8 bit
- Zoom: 8 or 16bit
- Focus: 8 or 16bit
- Dimmer: 8 or 16bit
- Ethernet port: Art-Net, MA Net, MA Net 2 protocols, ready for ACN
- Data in/out: Locking 3-pin & 5-pin XLR
- Power input: Neutrik PowerCon
- Built-in analyser for easy fault finding

ROTATING GOBOS

- Glass gobos - outside diameter: 15,9 mm, image diameter: 12,5 mm, thickness: 1.1 mm, high temperature borofloat or better glass

STATIC - BEAM GOBOS

- Aluminium gobo wheel - thickness: 0,5 mm, gobo image diameter: 6 mm

THERMAL SPECIFICATION

- Maximum ambient temperature: 45 °C (104 °F)
- Maximum surface temperature: 100 °C (212 °F)

ELECTRICAL SPECIFICATION

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: 470 W at 230 V / 50 Hz



MECHANICAL SPECIFICATION

- Height: 575 mm (22.6") - head in vertical position
- Width: 364 mm (14.3")
- Depth: 250 mm (9.8")
- Weight: 15 kg (33 lbs)
- Fixation option: Pan/Tilt-lock mechanism

RIGGING

- Mounting points: 2 pairs of ¼-turn locks
- 2 x Omega bracket with ¼-turn quick locks
- 1 x Safety attachment point

gobos & colours

ROTATING GOBO WHEEL



15020276




15020277



15020278



15020279



15020280



15020281



15020282



15020283



15020284

COLOUR WHEEL



14070356



14070357



14070358



14070359



14070360



14070368



14070361



14070362



14070363



14070364



14070365



14070366



14070367

FIXED GOBO WHEEL



99013881